

Safety Data Sheet

according to Regulation (EC) No 1907/2006

VITAFOL H Hardener

Revision date:

Product code: 059

Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

VITAFOL H Hardener

UFI: 1F00-Q072-G00Q-4PKC

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Use as laboratory reagent

1.3. Details of the supplier of the safety data sheet

Company name: VITA Zahnfabrik H.Rauter GmbH & Co.KG

Street: Spitalgasse 3

Place: D-79713 Bad Säckingen

Post-office box: 1338

D-79704 Bad Säckingen

Telephone: +49(0)7761-562-0

Telefax: +49(0)7761-562-299

e-mail: info@vita-zahnfabrik.com

Contact person: regulatory affairs

e-mail: info@vita-zahnfabrik.com

Internet: www.vita-zahnfabrik.com

Responsible Department: Regulatory Affairs

1.4. Emergency telephone number:

+49-(0)761-19240

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Flammable liquid: Flam. Liq. 3

Acute toxicity: Acute Tox. 4

Serious eye damage/eye irritation: Eye Irrit. 2

Reproductive toxicity: Repr. 2

Specific target organ toxicity - single exposure: STOT SE 3

Specific target organ toxicity - repeated exposure: STOT RE 1

Hazard Statements:

Flammable liquid and vapour.

Harmful if inhaled.

Causes serious eye irritation.

Suspected of damaging the unborn child.

May cause respiratory irritation.

Causes damage to organs through prolonged or repeated exposure.

2.2. Label elements**Regulation (EC) No. 1272/2008****Hazard components for labelling**

ethyl silicate, tetraethyl silicate

tetraethyl silicate; ethyl silicate

Silicic acid (H₄SiO₄), tetraethyl ester, reaction products with bis(acetyloxy)dioctylstannane**Signal word:** Danger

Safety Data Sheet

according to Regulation (EC) No 1907/2006

VITAFOL H Hardener

Revision date:

Product code: 059

Page 2 of 10

Pictograms:**Hazard statements**

H226	Flammable liquid and vapour.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P337+P313	If eye irritation persists: Get medical advice/attention.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Hazardous components**

CAS No	Chemical name	Quantity
	EC No	Index No
	REACH No	
	GHS Classification	
78-10-4	ethyl silicate, tetraethyl silicate	80 - < 85 %
	201-083-8	014-005-00-0
		01-2119496195-28
	Flam. Liq. 3, Acute Tox. 4, Eye Irrit. 2, STOT SE 3; H226 H332 H319 H335	
93925-43-0	Silicic acid (H ₄ SiO ₄), tetraethyl ester, reaction products with bis(acetyloxy)dioctylstannane	10 - < 15 %
	300-346-5	
	Flam. Liq. 3, Repr. 2, Acute Tox. 4, Eye Irrit. 2, STOT RE 1, Aquatic Chronic 4; H226 H361d H302 H319 H372 H413	
68299-15-0	Bis(neodecanoyloxy)dioctylstannane	1 - < 5 %
	269-595-4	
	STOT RE 2, Aquatic Chronic 4; H373 H413	

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
78-10-4	201-083-8	ethyl silicate, tetraethyl silicate	80 - < 85 %
		inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1.5 mg/l (dusts or mists); dermal: LD50 = 5860 mg/kg	
93925-43-0	300-346-5	Silicic acid (H ₄ SiO ₄), tetraethyl ester, reaction products with bis(acetyloxy)dioctylstannane	10 - < 15 %
		oral: ATE = 500 mg/kg	

Safety Data Sheet

according to Regulation (EC) No 1907/2006

VITAFOL H Hardener

Revision date:

Product code: 059

Page 3 of 10

SECTION 4: First aid measures**4.1. Description of first aid measures****After inhalation**

Provide fresh air. Medical treatment necessary.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

Rinse mouth immediately and drink plenty of water. Induce vomiting when the affected person is not unconscious. Medical treatment necessary.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Carbon dioxide (CO₂), Foam, Extinguishing powder.

Unsuitable extinguishing media

Water.

5.2. Special hazards arising from the substance or mixture

Flammable. Vapours can form explosive mixtures with air.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Danger of explosion

6.3. Methods and material for containment and cleaning up**Other information**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

Safety Data Sheet

according to Regulation (EC) No 1907/2006

VITAFOL H Hardener

Revision date:

Product code: 059

Page 4 of 10

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaust at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational exposure limit values**

CAS No	Name of agent	ppm	mg/m ³	fib/cm ³	Category	Origin
78-10-4	Tetraethyl orthosilicate	5	44		TWA (8 h)	

8.2. Exposure controls**Appropriate engineering controls**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Suitable eye protection: goggles.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Recommended glove articles KCK Dermatrill P NBR (Nitrile rubber) Breakthrough time: 30 min

Skin protection

Wear suitable protective clothing.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

VITAFOL H Hardener

Revision date:

Product code: 059

Page 5 of 10

Respiratory protection

Technical ventilation of workplace Provide adequate ventilation as well as local exhaustion at critical locations.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	light red
Odour:	characteristic

Changes in the physical state

Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	166 °C
Flash point:	37 °C

Flammability

Solid/liquid:	not applicable
Gas:	not applicable
Lower explosion limits:	not determined
Upper explosion limits:	not determined

Self-ignition temperature

Solid:	not applicable
Gas:	not applicable
Decomposition temperature:	not determined
pH-Value:	not determined
Water solubility:	No

Solubility in other solvents

not determined	
Partition coefficient n-octanol/water:	not determined
Vapour pressure: (at 50 °C)	<=1100 hPa
Density:	not determined
Relative vapour density:	not determined

9.2. Other information**Information with regard to physical hazard classes**

Oxidizing properties
Not oxidising.

Other safety characteristics

Solid content:	0,0 %
Evaporation rate:	not determined

Further Information**SECTION 10: Stability and reactivity****10.1. Reactivity**

Flammable.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

VITAFOL H Hardener

Revision date:

Product code: 059

Page 6 of 10

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity**

Harmful if inhaled.

ATEmix calculated

ATE (inhalation vapour) 13,10 mg/l; ATE (inhalation aerosol) 1,786 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
78-10-4	ethyl silicate, tetraethyl silicate				
	dermal	LD50 mg/kg	5860		
	inhalation vapour	ATE	11 mg/l		
	inhalation aerosol	ATE	1.5 mg/l		
93925-43-0	Silicic acid (H4SiO4), tetraethyl ester, reaction products with bis(acetyloxy)dioctylstannane				
	oral	ATE mg/kg	500		

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of damaging the unborn child. (Silicic acid (H4SiO4), tetraethyl ester, reaction products with bis(acetyloxy)dioctylstannane)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. (ethyl silicate, tetraethyl silicate)

STOT-repeated exposure

Causes damage to organs through prolonged or repeated exposure. (Silicic acid (H4SiO4), tetraethyl ester, reaction products with bis(acetyloxy)dioctylstannane)

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Safety Data Sheet

according to Regulation (EC) No 1907/2006

VITAFOL H Hardener

Revision date:

Product code: 059

Page 7 of 10

SECTION 12: Ecological information**12.1. Toxicity**

The product is not: Ecotoxic.

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The product has not been tested.

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

Contaminated packaging

This material and its container must be disposed of as hazardous waste. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information**Land transport (ADR/RID)**

<u>14.1. UN number or ID number:</u>	UN 1292
<u>14.2. UN proper shipping name:</u>	TETRAETHYL SILICATE
<u>14.3. Transport hazard class(es):</u>	3
<u>14.4. Packing group:</u>	III
Hazard label:	3



Classification code:	F1
Limited quantity:	5 L
Excepted quantity:	E1
Transport category:	3
Hazard No:	30
Tunnel restriction code:	D/E

Inland waterways transport (ADN)

<u>14.1. UN number or ID number:</u>	UN 1292
<u>14.2. UN proper shipping name:</u>	TETRAETHYL SILICATE
<u>14.3. Transport hazard class(es):</u>	3

Safety Data Sheet

according to Regulation (EC) No 1907/2006

VITAFOL H Hardener

Revision date:

Product code: 059

Page 8 of 10

14.4. Packing group:

III

Hazard label:

3



Classification code:

F1

Limited quantity:

5 L

Excepted quantity:

E1

Marine transport (IMDG)**14.1. UN number or ID number:**

UN 1292

14.2. UN proper shipping name:

TETRAETHYL SILICATE

14.3. Transport hazard class(es):

3

14.4. Packing group:

III

Hazard label:

3



Special Provisions:

-

Limited quantity:

5 L

Excepted quantity:

E1

EmS:

F-E, S-D

Air transport (ICAO-TI/IATA-DGR)**14.1. UN number or ID number:**

UN 1292

14.2. UN proper shipping name:

TETRAETHYL SILICATE

14.3. Transport hazard class(es):

3

14.4. Packing group:

III

Hazard label:

3



Limited quantity Passenger:

10 L

Passenger LQ:

Y344

Excepted quantity:

E1

IATA-packing instructions - Passenger:

355

IATA-max. quantity - Passenger:

60 L

IATA-packing instructions - Cargo:

366

IATA-max. quantity - Cargo:

220 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS:

No

14.6. Special precautions for user

Warning: Combustible liquid.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Safety Data Sheet

according to Regulation (EC) No 1907/2006

VITAFOL H Hardener

Revision date:

Product code: 059

Page 9 of 10

EU regulatory information

Restrictions on use (REACH, annex XVII):
Entry 3, Entry 40

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Abbreviations and acronyms**

ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
Acute Tox. 4; H332	Calculation method
Eye Irrit. 2; H319	Calculation method
Repr. 2; H361d	Calculation method
STOT SE 3; H335	Calculation method
STOT RE 1; H372	Calculation method

Relevant H and EUH statements (number and full text)

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H413	May cause long lasting harmful effects to aquatic life.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

VITAFOL H Hardener

Revision date:

Product code: 059

Page 10 of 10

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)