

according to Regulation (EC) No 1907/2006

VITAFOL H Hardener

Revision date: 10.07.2023

Product code: 059

Page 1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

VITAFOL H Hardener

UFI:

1F00-Q072-G00Q-4PKC

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Use as laboratory reagent

1.3. Details of the supplier of the safety data sheet

Company name:	VITA Zahnfabrik H.Rauter GmbH & Co.KG	
Street:	Spitalgasse 3	
Place:	D-79713 Bad Säckingen	
Post-office box:	1338	
	D-79704 Bad Säckingen	
Telephone:	+49(0)7761-562-0	Telefax:+49(0)7761-562-299
E-mail:	info@vita-zahnfabrik.com	
Contact person:	regulatory affairs	
E-mail:	info@vita-zahnfabrik.com	
Internet:	www.vita-zahnfabrik.com	
Responsible Department:	Regulatory Affairs	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Flam. Liq. 3; H226 Acute Tox. 4; H332 Eye Irrit. 2; H319 Repr. 2; H361d STOT SE 3; H335 STOT RE 1; H372

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling ethyl silicate, tetraethyl silicate tetraethyl silicate; ethyl silicate Silicic acid (H4SiO4), tetraethyl ester, reaction products with bis(acetyloxy)dioctylstannane

Signal word: Pictograms:





Hazard statements

H226	Flammable liquid and vapour.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.



according to Regulation (EC) No 1907/2006

VITAFOL H Hardener				
Revision date: 10.07.2023	Product code: 059	Page 2 of 9		
H361d	Suspected of damaging the unborn child.			
H372	Causes damage to organs through prolonged or repeated exposure.			
Precautionary statemer	nts			
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.			
P260	Do not breathe dust/fume/gas/mist/vapours/spray.			
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection	l.		
P337+P313	If eye irritation persists: Get medical advice/attention.			
2.3. Other hazards				

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No	1272/2008)		
78-10-4	ethyl silicate, tetraethyl silicate			80 - < 85 %
	201-083-8	014-005-00-0	01-2119496195-28	
	Flam. Liq. 3, Acute Tox. 4, Eye Irri	t. 2, STOT SE 3; H226 H332 H319 H	335	
93925-43-0	Silicic acid (H4SiO4), tetraethyl ester, reaction products with bis(acetyloxy)dioctylstannane		xy)dioctylstannane	10 - < 15 %
	300-346-5			
	Flam. Liq. 3, Repr. 2, Acute Tox. 4 H319 H372 H413	, Eye Irrit. 2, STOT RE 1, Aquatic Ch	ronic 4; H226 H361d H302	
68299-15-0	Bis(neodecanoyloxy)dioctylstanna		1 - < 5 %	
	269-595-4			
	STOT RE 2, Aquatic Chronic 4; H3	373 H413		

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc	Limits, M-factors and ATE	
78-10-4	201-083-8	ethyl silicate, tetraethyl silicate	80 - < 85 %
	inhalation: AT = 5860 mg/kg	E = 11 mg/l (vapours); inhalation: ATE = 1.5 mg/l (dusts or mists); dermal: LD50	
93925-43-0	300-346-5	Silicic acid (H4SiO4), tetraethyl ester, reaction products with bis(acetyloxy)dioctylstannane	10 - < 15 %
oral: ATE = 500 mg/kg			

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation

Provide fresh air. Medical treatment necessary.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

Rinse mouth immediately and drink plenty of water. Induce vomiting when the affected person is not



according to Regulation (EC) No 1907/2006

VITAFOL H Hardener

Revision date: 10.07.2023

Product code: 059

Page 3 of 9

unconscious. Medical treatment necessary.

<u>4.2. Most important symptoms and effects, both acute and delayed</u> No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2), Foam, Extinguishing powder.

Unsuitable extinguishing media

Water.

5.2. Special hazards arising from the substance or mixture

Flammable. Vapours can form explosive mixtures with air.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Danger of explosion

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash



according to Regulation (EC) No 1907/2006

VITAFOL H Hardener

Revision date: 10.07.2023

Product code: 059

Page 4 of 9

hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaustion at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
78-10-4	Tetra-ethyl-orthosilicate	5	44		TWA (8 h)	

8.2. Exposure controls





Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection: goggles.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Recommended glove articles KCK Dermatril P NBR (Nitrile rubber) Breakthrough time: 30 min

Skin protection

Wear suitable protective clothing.

Respiratory protection

Technical ventilation of workplace Provide adequate ventilation as well as local exhaustion at critical locations.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	light red	
Odour:	characteristic	
Melting point/freezing point:		not determined
Boiling point or initial boiling point and		166 °C
boiling range:		



according to Regulation (EC) No 1907/2006

VI	TAFOL H Hardener	
Revision date: 10.07.2023	Product code: 059	Page 5 of §
Flammability:	not applicable not applicable	
Lower explosion limits:	not determined	
Upper explosion limits:	not determined	
Flash point:	37 °C	
Decomposition temperature:	not determined	
pH-Value:	not determined	
Water solubility: Solubility in other solvents	No	
not determined		
Partition coefficient n-octanol/water:	not determined	
Vapour pressure: (at 50 °C)	<=1100 hPa	
Density:	not determined	
Relative vapour density:	not determined	
0.2. Other information		
Information with regard to physical hazard classes Self-ignition temperature		
Solid:	not applicable	
Gas:	not applicable	
Oxidizing properties Not oxidising.		
Other safety characteristics		
Evaporation rate:	not determined	
Solid content:	0,0 %	

-

10.1. Reactivity

Flammable.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Harmful if inhaled.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) 0.0000 mg/l; ATE (inhalation dust/mist) 1786.00000 mg/l



according to Regulation (EC) No 1907/2006

VITAFOL H Hardener

Revision date: 10.07.2023

Product code: 059

Page 6 of 9

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
78-10-4	ethyl silicate, tetraethyl si	licate		-		
	dermal	LD50 mg/kg	5860			
	inhalation vapour	ATE	11 mg/l			
	inhalation dust/mist	ATE	1.5 mg/l			
93925-43-0	Silicic acid (H4SiO4), tetraethyl ester, reaction products with bis(acetyloxy)dioctylstannane					
	oral	ATE mg/kg	500			

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of damaging the unborn child. (Silicic acid (H4SiO4), tetraethyl ester, reaction products with

bis(acetyloxy)dioctylstannane)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. (ethyl silicate, tetraethyl silicate)

STOT-repeated exposure

Causes damage to organs through prolonged or repeated exposure. (Silicic acid (H4SiO4), tetraethyl ester, reaction products with bis(acetyloxy)dioctylstannane)

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

The product is not: Ecotoxic.

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII. The product has not been tested.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.



according to Regulation (EC) No 1907/2006

VITAFOL H Hardener

Revision date: 10.07.2023

Product code: 059

Page 7 of 9

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

Contaminated packaging

This material and its container must be disposed of as hazardous waste. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

<u>14.1. UN number or ID number:</u>	UN 1292
14.2. UN proper shipping name:	TETRAETHYL SILICATE
14.3. Transport hazard class(es):	3
14.4. Packing group:	III
Hazard label:	3
Classification code:	F1
Limited quantity:	5 L
Excepted quantity:	E1
Transport category:	3
Hazard No:	30
Tunnel restriction code:	D/E
Inland waterways transport (ADN)	LIN 4202
14.1. UN number or ID number:	UN 1292 TETRAETHYL SILICATE
14.2. UN proper shipping name:	-
14.3. Transport hazard class(es):	3
14.4. Packing group:	
Hazard label:	3
Classification code:	F1
Limited quantity:	5 L
Excepted quantity:	E1
Marine transport (IMDG)	
<u>14.1. UN number or ID number:</u> <u>14.2. UN proper shipping name:</u> <u>14.3. Transport hazard class(es):</u> <u>14.4. Packing group:</u>	UN 1292 TETRAETHYL SILICATE 3 III
Hazard label:	3



according to Regulation (EC) No 1907/2006

	VITAFOL H Hardener	
Revision date: 10.07.2023	Product code: 059	Page 8 of 9
Special Dravisiana		
Special Provisions: Limited quantity:	- 5 L	
Excepted quantity:	E1	
EmS:	F-E, S-D	
Air transport (ICAO-TI/IATA-DGR)		
<u>14.1. UN number or ID number:</u>	UN 1292	
14.2. UN proper shipping name:	TETRAETHYL SILICATE	
<u>14.3. Transport hazard class(es):</u>	3	
14.4. Packing group:	III	
Hazard label:	3	
	3	
Limited quantity Passenger:	10 L	
Passenger LQ:	Y344	
Excepted quantity:	E1	
IATA-packing instructions - Passenger:	355	
IATA-max. quantity - Passenger:	60 L	
IATA-packing instructions - Cargo:	366	
IATA-max. quantity - Cargo:	220 L	
14.5. Environmental hazards		
ENVIRONMENTALLY HAZARDOUS:	No	
14.6. Special precautions for user		
Warning: Combustible liquid.		
14.7. Maritime transport in bulk according to	IMO instruments	
not applicable		
SECTION 15: Regulatory information		
15.1 Safety health and environmental regul	ations/legislation specific for the substance or mixture	
EU regulatory information		
Restrictions on use (REACH, annex XVII): Entry 3, Entry 40		
National regulatory information		
Employment restrictions:	Observe restrictions to employment for juveniles according to the 'juver	nile
	work protection guideline' (94/33/EC). Observe employment restrictions	
	under the Maternity Protection Directive (92/85/EEC) for expectant or	
	nursing mothers.	
Water hazard class (D):	2 - obviously hazardous to water	
15.2. Chemical safety assessment		
· · · · · · · · · · · · · · · · · · ·	ances in this mixture were not carried out.	

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1.



according to Regulation (EC) No 1907/2006

VITAFOL H Hardener

Revision date: 10.07.2023

Product code: 059

Page 9 of 9

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Flam. Liq: Flammable liquid

Acute Tox: Acute toxicity

Eye Irrit: Eye irritation

Repr: Reproductive toxicity

STOT SE: Specific target organ toxicity - single exposure

STOT RE: Specific target organ toxicity - repeated exposure

Aquatic Chronic: Chronic aquatic hazard

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
Acute Tox. 4; H332	Calculation method
Eye Irrit. 2; H319	Calculation method
Repr. 2; H361d	Calculation method
STOT SE 3; H335	Calculation method
STOT RE 1; H372	Calculation method

Relevant H and EUH statements (number and full text)

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H413	May cause long lasting harmful effects to aquatic life.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)