



according to Regulation (EC) No 1907/2006

VITAVM LC SEPARATOR

Revision date: 20.02.2017 Product code: 152-CLP Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

VITAVM LC SEPARATOR

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Use as laboratory reagent

1.3. Details of the supplier of the safety data sheet

Company name: VITA Zahnfabrik H. Rauter GmbH & Co. KG

Post-office box: 1338

79704 Bad Säckingen

+49-(0)761-19240

Telephone: +49(0)7761-562-0 Telefax: +49(0)7761-562-299

e-mail: info@vita-zahnfabrik.com Internet: www.vita-zahnfabrik.com

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

1.4. Emergency telephone

Flammable liquid: Flam. Liq. 2 Aspiration hazard: Asp. Tox. 1 Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Dam. 1

Reproductive toxicity: Repr. 2

Specific target organ toxicity - single exposure: STOT SE 3 Specific target organ toxicity - repeated exposure: STOT RE 2 Hazardous to the aquatic environment: Aquatic Acute 1 Hazardous to the aquatic environment: Aquatic Chronic 1

Hazard Statements:

Highly flammable liquid and vapour.

May be fatal if swallowed and enters airways.

Causes skin irritation.

Causes serious eye damage.

Suspected of damaging the unborn child. May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

Very toxic to aquatic life.

Very toxic to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

cyclohexane toluene

methylsilanetriyl triacetat

Signal word: Danger



according to Regulation (EC) No 1907/2006

VITAVM LC SEPARATOR

Revision date: 20.02.2017 Product code: 152-CLP Page 2 of 10

Pictograms:











Hazard statements

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.
 H318 Causes serious eye damage.
 H336 May cause drowsiness or dizziness.
 H361d Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P312 Call a POISON CENTER/doctor if you feel unwell.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

| CAS No | Chemical name | Quantity | | |
|-----------|--|------------------------|------------------|-----------|
| | EC No | Index No | REACH No | |
| | Classification according to Regulat | • | | |
| 110-82-7 | cyclohexane | | 50 - < 55 % | |
| | 203-806-2 | 601-017-00-1 | 01-2119463273-41 | |
| | Flam. Liq. 2, Skin Irrit. 2, STOT SE H315 H336 H304 H400 H410 | uatic Chronic 1; H225 | | |
| 108-88-3 | toluene | | 10 - < 15 % | |
| | 203-625-9 | 601-021-00-3 | 05-2114615130-69 | |
| | Flam. Liq. 2, Repr. 2, Skin Irrit. 2, 9 H373 H304 | ; H225 H361d H315 H336 | | |
| 4253-34-3 | methylsilanetriyl triacetat | | | 1 - < 5 % |
| | 224-221-9 | | | |
| | Acute Tox. 4, Skin Corr. 1B; H302 | | | |
| 1067-33-0 | dibutyltin diacetate | | < 1 % | |
| | 213-928-8 | | | |
| | Acute Tox. 2, Skin Irrit. 2, Eye Irrit. | 35 | | |

Full text of H and EUH statements: see section 16.





according to Regulation (EC) No 1907/2006

VITAVM LC SEPARATOR

Revision date: 20.02.2017 Product code: 152-CLP Page 3 of 10

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation

Provide fresh air. Medical treatment necessary.

After contact with skin

After contact with skin, wash immediately with polyethylene glycol, followed by plenty of water. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2), Foam, Extinguishing powder.

Unsuitable extinguishing media

Water.

5.2. Special hazards arising from the substance or mixture

Highly flammable. Vapours can form explosive mixtures with air.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Danger of explosion

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling



according to Regulation (EC) No 1907/2006

VITAVM LC SEPARATOR

Revision date: 20.02.2017 Product code: 152-CLP Page 4 of 10

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

Keep away from sources of ignition. - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaustion at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Advice on storage compatibility

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances.

7.3. Specific end use(s)

Use as laboratory reagent

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values

| CAS No | Name of agent | ppm | mg/m³ | fib/cm³ | Category | Origin |
|----------|---------------|-----|-------|---------|---------------|--------|
| 110-82-7 | Cyclohexane | 200 | 700 | | TWA (8 h) | |
| | | - | - | | STEL (15 min) | |
| 108-88-3 | Toluene | 50 | 192 | | TWA (8 h) | |
| | | 100 | 384 | | STEL (15 min) | |

8.2. Exposure controls









Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Eye/face protection

Suitable eye protection: goggles.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Recommended glove articles KCL Dermatril P Breakthrough time (maximum wearing time) 60 min NBR (Nitrile rubber)



according to Regulation (EC) No 1907/2006

VITAVM LC SEPARATOR

Revision date: 20.02.2017 Product code: 152-CLP Page 5 of 10

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Technical ventilation of workplace Provide adequate ventilation as well as local exhaustion at critical locations.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid
Colour: translucent
Odour: characteristic

Test method

pH-Value: not determined

Changes in the physical state

Melting point: not determined Initial boiling point and boiling range: 77 $^{\circ}$ C Flash point: <5 $^{\circ}$ C

Flammability

Solid: not applicable
Gas: not applicable
Lower explosion limits: 1,2 vol. %
Upper explosion limits: 8,3 vol. %

Ignition temperature: 260 °C DIN 51794

Auto-ignition temperature

Solid: not applicable
Gas: not applicable

Decomposition temperature: not determined

Oxidizing properties

Not oxidizing.

Vapour pressure: <=1100 hPa

(at 50 °C)

Density: 0,86700 g/cm³ Water solubility: No

Solubility in other solvents

not determined

Partition coefficient: not determined
Vapour density: not determined
Evaporation rate: not determined

9.2. Other information

Solid content: 0,0 %

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable.



according to Regulation (EC) No 1907/2006

VITAVM LC SEPARATOR

Revision date: 20.02.2017 Product code: 152-CLP Page 6 of 10

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

| CAS No | Chemical name | | | | | | | |
|-----------|-----------------------------|---------------|----------|---------|--------|--------|--|--|
| | Exposure route | Dose | | Species | Source | Method | | |
| 110-82-7 | cyclohexane | | | | | | | |
| | dermal | LD50 mg/kg | 12705 | | | | | |
| 108-88-3 | toluene | | | | | | | |
| | dermal | LD50 mg/kg | 12124 | | | | | |
| 4253-34-3 | methylsilanetriyl triacetat | | | | | | | |
| | oral | ATE mg/kg | 500 | | | | | |
| 1067-33-0 | dibutyItin diacetate | | | | | | | |
| | oral | LD50 | 32 mg/kg | | | | | |
| | dermal | LD50 mg/kg | 2320 | | | | | |

Irritation and corrosivity

Causes skin irritation.

Causes serious eye damage.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of damaging the unborn child. (toluene)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (cyclohexane)

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (toluene)

Aspiration hazard

May be fatal if swallowed and enters airways. (cyclohexane; toluene)



according to Regulation (EC) No 1907/2006

VITAVM LC SEPARATOR

Revision date: 20.02.2017 Product code: 152-CLP Page 7 of 10

Additional information on tests

This mixture is classified as hazardous according to regulation (EC) No. 1272/2008 [CLP]. Special hazards arising from the substance or mixture!

SECTION 12: Ecological information

12.1. Toxicity

Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The product has not been tested.

12.6. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

Contaminated packaging

This material and its container must be disposed of as hazardous waste. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (cyclohexane)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Classification code: F1

Special Provisions: 274 601 640D

Limited quantity: 1 L
Excepted quantity: E2
Transport category: 2
Hazard No: 33
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number: UN 1993



according to Regulation (EC) No 1907/2006

VITAVM LC SEPARATOR

Revision date: 20.02.2017 Product code: 152-CLP Page 8 of 10

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (cyclohexane)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Classification code: F1

Special Provisions: 274 601 640D

Limited quantity: 1 L
Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number: UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (cyclohexane)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Special Provisions: 274
Limited quantity: 1 L
Excepted quantity: E2
EmS: F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (cyclohexane)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Special Provisions:

Limited quantity Passenger:

Passenger LQ:

Excepted quantity:

A3

1 L

Y341

Excepted quantity:

E2

IATA-packing instructions - Passenger:353IATA-max. quantity - Passenger:5 LIATA-packing instructions - Cargo:364IATA-max. quantity - Cargo:60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: yes



Danger releasing substance: cyclohexane





according to Regulation (EC) No 1907/2006

VITAVM LC SEPARATOR

Revision date: 20.02.2017 Product code: 152-CLP Page 9 of 10

14.6. Special precautions for user

Warning: Combustible liquid.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 48: toluene Entry 57: cyclohexane

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water contaminating class (D): 2 - water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.

H300 Fatal if swallowed. H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways. H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H318 Causes serious eye damage.
 H319 Causes serious eye irritation.
 H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.
 H361d Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.


H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

EUH014 Reacts violently with water.

Further Information

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for





according to Regulation (EC) No 1907/2006

VITAVM LC SEPARATOR

Revision date: 20.02.2017 Product code: 152-CLP Page 10 of 10

adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)