

### VITACOLL

Revision date: 26.01.2017

Product code: 040-CN

Page 1 of 9

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

VITACOLL

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Use as laboratory reagent

### 1.3. Details of the supplier of the safety data sheet

Company name: VITA Zahnfabrik H. Rauter GmbH & Co. KG

Post-office box: 1338

79704 Bad Säckingen

Telephone: +49(0)7761-562-0

Telefax: +49(0)7761-562-299

e-mail: info@vita-zahnfabrik.com

Internet: www.vita-zahnfabrik.com

### 1.4. Emergency telephone

+49-(0)761-19240

#### number:

#### Further Information

medical device

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### GB 30000-2013

Hazard categories:

Flammable liquid: Flam. Liq. 2

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2A

Respiratory or skin sensitisation: Skin Sens. 1

Specific target organ toxicity - single exposure: STOT SE 3

Specific target organ toxicity - single exposure: STOT SE 3

Hazard Statements:

Highly flammable liquid and vapour.

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause respiratory irritation.

May cause drowsiness or dizziness.

### 2.2. Label elements

#### GB 30000-2013

#### Hazard components for labelling

methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; methyl methacrylate

butanone; ethyl methyl ketone

Signal word: Danger

Pictograms:



#### Hazard statements

H225

Highly flammable liquid and vapour.

H315

Causes skin irritation.

## Safety Data Sheet

### VITACOLL

Revision date: 26.01.2017

Product code: 040-CN

Page 2 of 9

H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.

#### Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P235	Keep cool.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.

#### 2.3. Other hazards

No information available.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

##### Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
80-62-6	methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; methyl methacrylate			45 - < 50 %
	201-297-1	607-035-00-6	01-2119452498-28	
	Flam. Liq. 2, Skin Irrit. 2, Skin Sens. 1, STOT SE 3; H225 H315 H317 H335			
78-93-3	butanone; ethyl methyl ketone			45 - < 50 %
	201-159-0	606-002-00-3	01-2119457290-43	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			

Full text of H and EUH statements: see section 16.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### After inhalation

Provide fresh air. Medical treatment necessary.

##### After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

##### After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

##### After ingestion

Rinse mouth immediately and drink plenty of water.

#### 4.2. Most important symptoms and effects, both acute and delayed

No information available.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### VITACOLL

Revision date: 26.01.2017

Product code: 040-CN

Page 3 of 9

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

Carbon dioxide (CO<sub>2</sub>), Foam, Extinguishing powder.

#### Unsuitable extinguishing media

Water.

### 5.2. Special hazards arising from the substance or mixture

Highly flammable. Vapours can form explosive mixtures with air.

### 5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

#### Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

### 6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Danger of explosion

### 6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

#### Advice on protection against fire and explosion

Keep away from sources of ignition. - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

#### Advice on storage compatibility

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances.

### 7.3. Specific end use(s)

Use as laboratory reagent

## SECTION 8: Exposure controls/personal protection

### VITACOLL

Revision date: 26.01.2017

Product code: 040-CN

Page 4 of 9

#### 8.1. Control parameters

##### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
78-93-3	Butan-2-one (methyl ethyl ketone)	200	600		TWA (8 h)	WEL
		300	899		STEL (15 min)	WEL
80-62-6	Methyl methacrylate	50	208		TWA (8 h)	WEL
		100	416		STEL (15 min)	WEL

##### Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
78-93-3	Butan-2-one	butan-2-one	70 µmol/L	urine	Post shift

#### 8.2. Exposure controls



##### Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

##### Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

##### Eye/face protection

Suitable eye protection: goggles.

##### Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Recommended glove articles KCL Butoject Butyl caoutchouc (butyl rubber) Breakthrough time (maximum wearing time) 60 min

##### Skin protection

Wear suitable protective clothing.

##### Respiratory protection

Technical ventilation of workplace Provide adequate ventilation as well as local exhaustion at critical locations.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	colourless
Odour:	characteristic

**Test method**

## Safety Data Sheet

### VITACOLL

Revision date: 26.01.2017

Product code: 040-CN

Page 5 of 9

pH-Value: not determined

#### Changes in the physical state

Melting point: not determined

Initial boiling point and boiling range: 79 °C

Flash point: < -5 °C

#### Flammability

Solid: not applicable

Gas: not applicable

Lower explosion limits: 1,8 vol. %

Upper explosion limits: 12,5 vol. %

Ignition temperature: 430 °C

#### Auto-ignition temperature

Solid: not applicable

Gas: not applicable

Decomposition temperature: not determined

#### Oxidizing properties

Not oxidizing.

Vapour pressure: <=1100 hPa  
(at 50 °C)

Density: 0,87200 g/cm<sup>3</sup>

Water solubility: No

#### Solubility in other solvents

not determined

Partition coefficient: not determined

Vapour density: not determined

Evaporation rate: not determined

#### 9.2. Other information

Solid content: 0,0 %

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

Highly flammable.

#### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

#### 10.3. Possibility of hazardous reactions

No known hazardous reactions.

#### 10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

#### 10.5. Incompatible materials

No information available.

#### 10.6. Hazardous decomposition products

No known hazardous decomposition products.

### VITACOLL

Revision date: 26.01.2017

Product code: 040-CN

Page 6 of 9

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
80-62-6	methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; methyl methacrylate				
	dermal	LD50 mg/kg	>5000		
78-93-3	butanone; ethyl methyl ketone				
	dermal	LD50 mg/kg	5000		

#### Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

#### Sensitising effects

May cause an allergic skin reaction. (methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; methyl methacrylate)

#### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

#### STOT-single exposure

May cause respiratory irritation. (methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; methyl methacrylate)

May cause drowsiness or dizziness. (butanone; ethyl methyl ketone)

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

#### Additional information on tests

This mixture is classified as hazardous according to regulation (EC) No. 1272/2008 [CLP].

## SECTION 12: Ecological information

### 12.1. Toxicity

The product is not: Ecotoxic.

### 12.2. Persistence and degradability

The product has not been tested.

### 12.3. Bioaccumulative potential

The product has not been tested.

### 12.4. Mobility in soil

The product has not been tested.

### 12.5. Results of PBT and vPvB assessment

The product has not been tested.

### 12.6. Other adverse effects

No information available.

#### Further information

Avoid release to the environment.

### VITACOLL

Revision date: 26.01.2017

Product code: 040-CN

Page 7 of 9

#### SECTION 13: Disposal considerations

##### 13.1. Waste treatment methods

###### Advice on disposal


Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

###### Contaminated packaging


Handle contaminated packages in the same way as the substance itself.

#### SECTION 14: Transport information

##### Land transport (ADR/RID)

<b>14.1. UN number:</b>	UN 1993
<b>14.2. UN proper shipping name:</b>	FLAMMABLE LIQUID, N.O.S. (methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; methyl methacrylate; butanone; ethyl methyl ketone)
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3
	
Classification code:	F1
Special Provisions:	274 601 640D
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	33
Tunnel restriction code:	D/E

##### Inland waterways transport (ADN)

<b>14.1. UN number:</b>	UN 1993
<b>14.2. UN proper shipping name:</b>	FLAMMABLE LIQUID, N.O.S. (methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; methyl methacrylate; butanone; ethyl methyl ketone)
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3
	
Classification code:	F1
Special Provisions:	274 601 640D
Limited quantity:	1 L
Excepted quantity:	E2

##### Marine transport (IMDG)

<b>14.1. UN number:</b>	UN 1993
<b>14.2. UN proper shipping name:</b>	FLAMMABLE LIQUID, N.O.S. (methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; methyl methacrylate; butanone; ethyl methyl ketone)
<b>14.3. Transport hazard class(es):</b>	3

## Safety Data Sheet

### VITACOLL

Revision date: 26.01.2017

Product code: 040-CN

Page 8 of 9

**14.4. Packing group:**

II

Hazard label:

3



Special Provisions:

274

Limited quantity:

1 L

Excepted quantity:

E2

EmS:

F-E, S-E

**Air transport (ICAO-TI/IATA-DGR)**

**14.1. UN number:**

UN 1993

**14.2. UN proper shipping name:**

FLAMMABLE LIQUID, N.O.S. (methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; methyl methacrylate; butanone; ethyl methyl ketone)

**14.3. Transport hazard class(es):**

3

**14.4. Packing group:**

II

Hazard label:

3



Special Provisions:

A3

Limited quantity Passenger:

1 L

Passenger LQ:

Y341

Excepted quantity:

E2

IATA-packing instructions - Passenger:

353

IATA-max. quantity - Passenger:

5 L

IATA-packing instructions - Cargo:

364

IATA-max. quantity - Cargo:

60 L

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: no

**14.6. Special precautions for user**

Warning: Combustible liquid.

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

not applicable

## SECTION 15: Regulatory information

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**National regulatory information**

Employment restrictions:

Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Water contaminating class (D):

1 - slightly water contaminating

Skin resorption/Sensitization:

Causes allergic hypersensitivity reactions.

**15.2. Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.

## SECTION 16: Other information



### VITACOLL

Revision date: 26.01.2017

Product code: 040-CN

Page 9 of 9

#### Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route  
(European Agreement concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
GHS: Globally Harmonized System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service  
LC50: Lethal concentration, 50%  
LD50: Lethal dose, 50%

#### Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.

#### Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

---

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*