

Safety Data Sheet

according to 29 CFR 1910.1200(g)

VITAFOL H Hardener

Revision date: 18.09.2019

Product code: 059

Page 1 of 8

1. Identification

Product identifier

VITAFOL H Hardener

Recommended use of the chemical and restrictions on use

Use of the substance/mixture

Use as laboratory reagent

Details of the supplier of the safety data sheet

Company name: VITA Zahnfabrik H.Rauter GmbH & Co.KG

Post-office box: 1338
79704 Bad Säckingen

Telephone: +49(0)7761-562-0

Telefax: +49(0)7761-562-299

e-mail: info@vita-zahnfabrik.com

Internet: www.vita-zahnfabrik.com

Emergency phone number: +49-(0)761-19240

2. Hazard(s) identification

Classification of the chemical

29 CFR Part 1910.1200

Flammable liquids: Flam. Liq. 3

Acute toxicity: Acute Tox. 4 (inhalation)

Serious eye damage/eye irritation: Eye Irrit. 2A

Specific target organ toxicity single exposure: STOT SE 3 (respiratory tract irritation)

Specific target organ toxicity repeated or prolonged exposure: STOT RE 2

Label elements

29 CFR Part 1910.1200

Signal word: Warning**Pictograms:**

Hazard statements

Flammable liquid and vapor

Causes serious eye irritation

Harmful if inhaled

May cause respiratory irritation

May cause damage to organs through prolonged or repeated exposure

Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wear protective gloves/protective clothing/eye protection/face protection.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

If eye irritation persists: Get medical advice/attention.

Store in a well-ventilated place. Keep cool.

Hazards not otherwise classified

No information available.

Safety Data Sheet

according to 29 CFR 1910.1200(g)

VITAFOL H Hardener

Revision date: 18.09.2019

Product code: 059

Page 2 of 8

3. Composition/information on ingredients

Mixtures

Hazardous components

CAS No	Components	Quantity
78-10-4	ethyl silicate, tetraethyl silicate	60 %
78-10-4	tetraethyl silicate; ethyl silicate	24 %
93925-43-0	Silicic acid (H ₄ SiO ₄), tetraethyl ester, reaction products with bis(acetyloxy)dioctylstannane	12 %
68299-15-0	Bis(neodecanoyloxy)dioctylstannane	2 %

4. First-aid measures

Description of first aid measures

After inhalation

Provide fresh air. Medical treatment necessary.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

Rinse mouth immediately and drink plenty of water. Induce vomiting when the affected person is not unconscious. Medical treatment necessary.

Most important symptoms and effects, both acute and delayed

No information available.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂), Foam, Extinguishing powder.

Unsuitable extinguishing media

Water.

Specific hazards arising from the chemical

Flammable. Vapors may form explosive mixtures with air.

Special protective equipment and precautions for fire-fighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray/stream to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Do not breathe gas/fume/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Danger of explosion

Safety Data Sheet

according to 29 CFR 1910.1200(g)

VITAFOL H Hardener

Revision date: 18.09.2019

Product code: 059

Page 3 of 8

Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

Reference to other sections

Safe handling: see section 7
 Personal protection equipment (PPE): see section 8
 Disposal: see section 13

7. Handling and storage

Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fume/vapour/spray.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapors may form explosive mixtures with air.

Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaust at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances.

8. Exposure controls/personal protection

Control parameters

Exposure limits

CAS No.	Substance	ppm	mg/m ³	f/cc	Category	Origin
78-10-4	Ethyl silicate	100	850		TWA (8 h)	PEL
		10	85		TWA (8 h)	REL

Exposure controls



Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fume/vapour/spray.

Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Eye/face protection

Suitable eye protection: goggles.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the

Safety Data Sheet

according to 29 CFR 1910.1200(g)

VITAFOL H Hardener

Revision date: 18.09.2019

Product code: 059

Page 4 of 8

specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Recommended glove articles KCK Dermatril P NBR (Nitrile rubber) Breakthrough time (maximum wearing time) 30 min

Skin protection

Wear suitable protective clothing.

Respiratory protection

Technical ventilation of workplace Provide adequate ventilation as well as local exhaust at critical locations.

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical state:	Liquid	
Color:	light red	
Odor:	characteristic	
pH-Value:		not determined

Changes in the physical state

Melting point/freezing point:	not determined
Initial boiling point and boiling range:	166 °C
Flash point:	37 °C

Flammability

Solid:	not applicable
Gas:	not applicable
Lower explosion limits:	not determined
Upper explosion limits:	not determined

Auto-ignition temperature

Solid:	not applicable
Gas:	not applicable
Decomposition temperature:	not determined

Oxidizing properties

Not oxidising.	
Vapor pressure: (at 50 °C)	<=1100 hPa
Density:	not determined
Water solubility:	No

Solubility in other solvents

not determined	
Partition coefficient:	not determined
Vapor density:	not determined
Evaporation rate:	not determined

Other information

Solid content:	0,0 %
----------------	-------

10. Stability and reactivity

Reactivity

Flammable.

Chemical stability

Safety Data Sheet

according to 29 CFR 1910.1200(g)

VITAFOL H Hardener

Revision date: 18.09.2019

Product code: 059

Page 5 of 8

The product is stable under storage at normal ambient temperatures.

Possibility of hazardous reactions

No known hazardous reactions.

Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapors may form explosive mixtures with air.

Incompatible materials

No information available.

Hazardous decomposition products

No known hazardous decomposition products.

11. Toxicological information

Information on toxicological effects

Acute toxicity

Harmful if inhaled

ATEmix calculated

ATE (inhalation vapour) 13,10 mg/l; ATE (inhalation aerosol) 1,786 mg/l

CAS No	Components				
	Exposure route	Dose	Species	Source	Method
78-10-4	ethyl silicate, tetraethyl silicate				
	dermal	LD50 mg/kg	5860		
	inhalation vapour	ATE	11 mg/l		
	inhalation aerosol	ATE	1,5 mg/l		
78-10-4	tetraethyl silicate; ethyl silicate				
	oral	LD50 mg/kg	6270	Rat	GESTIS
	dermal	LD50 mg/kg	5880	Rabbit	GESTIS
	inhalation vapour	ATE	11 mg/l		
	inhalation aerosol	ATE	1,5 mg/l		
93925-43-0	Silicic acid (H4SiO4), tetraethyl ester, reaction products with bis(acetyloxy)dioctylstannane				
	oral	ATE mg/kg	500		

Irritation and corrosivity

Causes serious eye irritation

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitizing effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

Specific target organ toxicity (STOT) - single exposure

May cause respiratory irritation (ethyl silicate, tetraethyl silicate; tetraethyl silicate; ethyl silicate)

Specific target organ toxicity (STOT) - repeated exposure

May cause damage to organs through prolonged or repeated exposure (Bis(neodecanoyloxy)dioctylstannane)

Aspiration hazard

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to 29 CFR 1910.1200(g)

VITAFOL H Hardener

Revision date: 18.09.2019

Product code: 059

Page 6 of 8

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

12. Ecological information

Ecotoxicity

The product is not: Ecotoxic.

Persistence and degradability

The product has not been tested.

Bioaccumulative potential

The product has not been tested.

Mobility in soil

The product has not been tested.

Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

13. Disposal considerations

Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

Contaminated packaging

This material and its container must be disposed of as hazardous waste. Handle contaminated packages in the same way as the substance itself.

14. Transport information

Marine transport (IMDG)

<u>UN number:</u>	UN 1292
<u>UN proper shipping name:</u>	TETRAETHYL SILICATE
<u>Transport hazard class(es):</u>	3
<u>Packing group:</u>	III
Hazard label:	3



Special Provisions:	-
Limited quantity:	5 L
Excepted quantity:	E1
EmS:	F-E, S-D

Air transport (ICAO-TI/IATA-DGR)

<u>UN number:</u>	UN 1292
<u>UN proper shipping name:</u>	TETRAETHYL SILICATE
<u>Transport hazard class(es):</u>	3
<u>Packing group:</u>	III
Hazard label:	3

Safety Data Sheet

according to 29 CFR 1910.1200(g)

VITAFOL H Hardener

Revision date: 18.09.2019

Product code: 059

Page 7 of 8



Limited quantity Passenger:	10 L	
Passenger LQ:	Y344	
Excepted quantity:	E1	
IATA-packing instructions - Passenger:		355
IATA-max. quantity - Passenger:		60 L
IATA-packing instructions - Cargo:		366
IATA-max. quantity - Cargo:		220 L

Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

Special precautions for user

Warning: Combustible liquid.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

15. Regulatory information

U.S. Regulations

National regulatory information

SARA Section 311/312 Hazards:

ethyl silicate, tetraethyl silicate (78-10-4): Fire hazard, Immediate (acute) health hazard
 tetraethyl silicate; ethyl silicate (78-10-4): Fire hazard, Immediate (acute) health hazard
 Silicic acid (H₄SiO₄), tetraethyl ester, reaction products with bis(acetyloxy)dioctylstannane (93925-43-0):
 Fire hazard, Immediate (acute) health hazard, Delayed (chronic) health hazard
 Bis(neodecanoyloxy)dioctylstannane (68299-15-0): Delayed (chronic) health hazard

State Regulations

Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65, State of California)

This product can not expose you to chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

16. Other information

Revision date: 18.09.2019

Revision No: 3

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route
 (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonized System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service
 LC50: Lethal concentration, 50%
 LD50: Lethal dose, 50%

Other data

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of

Safety Data Sheet

according to 29 CFR 1910.1200(g)

VITAFOL H Hardener

Revision date: 18.09.2019

Product code: 059

Page 8 of 8

processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)